

## WHAT IS CLAIMED IS:

1. A side rack rod for motor vehicle, comprising:  
a straight tubular pipe section; a curved pipe section, respectively disposed  
on both ends of said straight tubular pipe section; a fixed base, disposed  
5 under each curved pipe section; characterized in that said fixed base  
comprising a long groove long thereon, and the maximum and minimum  
distance between said two long groove holes fitting in a range of various  
sizes.
2. A side rack rod for motor vehicle as claimed in claim 1, wherein said  
10 straight pipe section is hollow inside and interconnected.
3. A side rack rod for motor vehicle, comprising: a pair of corresponding  
anchors, each having a straight tubular section; a curved pipe section at both  
ends of said straight tubular section; a fixed base at each curved pipe section,  
and a sleeve disposed between two anchors; characterized in that said fixed  
15 base, each having a long groove hole, such that the maximum and minimum  
distances between said two long groove holes fitting a range of various  
sizes.
4. A side rack rod for motor vehicle as claimed in claim 3, wherein said sleeve  
is hollow and interconnected between said straight pipe section and curved  
20 pipe section of said anchor.
5. A side rack rod for motor vehicle as claimed in claim 3, wherein said  
straight pipe section of the anchor has a length larger than that of said  
sleeve.